

submittal date:

contact information

Name	
Phone Number	
Email	

company information *Unless otherwise noted, all reports will be issued in the name of the company listed above. If this needs to be different, please indicate this in the Comments section below*

Name	
Address	
Phone Number	

material information

Sample ID <i>This is the name that will be listed on the test report</i>			
Production Lot Number <i>if known</i>		Product Color	
Date Sample Taken <i>if known</i>		Sample Location <i>if known</i>	
Comments			

NOTE: All test specimens are discarded after the order is complete. If you wish to have the specimens or extra material returned, please note this in the comments box above. The client is responsible for all shipping charges.

testing required

<p><i>carpet testing</i></p> <ul style="list-style-type: none"> <input type="checkbox"/> binding sites ASTM D5793 <input type="checkbox"/> color to light AATCC 16.3, Opt.3 # of hours: _____ <input type="checkbox"/> dimensional stability ASTM D7570 <input type="checkbox"/> pile thickness ASTM D6859 <input type="checkbox"/> pile thickness ASTM D7241 <input type="checkbox"/> stain resistance AATCC 175 <input type="checkbox"/> tuft element length ASTM D6283 <input type="checkbox"/> tuft height ASTM D5823 <input type="checkbox"/> weight ASTM D5848 (total only) 	<p><i>ceramic tile testing</i></p> <ul style="list-style-type: none"> <input type="checkbox"/> abrasion resistance ASTM C1027 <input type="checkbox"/> breaking strength ASTM C648 <input type="checkbox"/> chemical resistance ASTM C650 <input type="checkbox"/> facial dimensions ASTM C499 <input type="checkbox"/> light reflectance ASTM C609 <input type="checkbox"/> staining resistance ASTM C1378 <input type="checkbox"/> static coefficient of friction ASTM C1028 <input type="checkbox"/> taber abrasion ASTM C501 (1,000 cycles) <input type="checkbox"/> warpage ASTM C485 <input type="checkbox"/> wedging ASTM C502
<p><i>laminated flooring testing</i></p> <ul style="list-style-type: none"> <input type="checkbox"/> cleanability / stain resistance NALFA 3.4 <input type="checkbox"/> dimensional tolerance NALFA 3.8 <input type="checkbox"/> light resistance NALFA 3.3 <input type="checkbox"/> static load NALFA 3.1 <input type="checkbox"/> thickness swell NALFA 3.2 <input type="checkbox"/> wear resistance NALFA 3.7 # of cycles: _____ (1,000 cycles, default) 	<p><i>wood flooring testing</i></p> <ul style="list-style-type: none"> <input type="checkbox"/> coating adhesion: tape test ASTM D3359 <input type="checkbox"/> method a ('X') <input type="checkbox"/> method b (cross-cut) <input type="checkbox"/> coefficient of friction ASTM D2394 <input type="checkbox"/> impact resistance ASTM D2794 <input type="checkbox"/> scratch resistance ASTM D2197 <input type="checkbox"/> taber abrasion ASTM D4060 # of cycles: _____ (1,000 cycles, default) wheel: _____ weight: _____
<p><i>resilient vinyl flooring testing</i></p> <ul style="list-style-type: none"> <input type="checkbox"/> chemical resistance ASTM F925 <input type="checkbox"/> color change: heat ASTM F1514 <input type="checkbox"/> color change: light ASTM F1515 # of hours: _____ <input type="checkbox"/> dimensional stability ASTM F2199 <input type="checkbox"/> emboss depth ASTM F373 <input type="checkbox"/> flexibility ASTM F137 <input type="checkbox"/> hardness: shore a ASTM D2240 <input type="checkbox"/> indentation + residual indentation ASTM F1914 	<ul style="list-style-type: none"> <input type="checkbox"/> size and squareness ASTM F2055 <input type="checkbox"/> static load resistance ASTM F970 <input type="checkbox"/> static resistance ASTM F150 <input type="checkbox"/> taber abrasion ASTM D3389 # of cycles: _____ (1,000 cycles, default) wheel: _____ weight: _____ <input type="checkbox"/> thickness ASTM F386 <input type="checkbox"/> thickness ASTM F387

NOTE: All tests are conditioned and tested at 73 ±3.5°F and 50 ±5% relative humidity, which is noted on the test report. This may reflect a deviation from what is specified in the ASTM standard. If alternate conditions are needed, include this requirement on the request form. Additional fees may apply.